

Klick&Show K-40 series Technical specification

Klick&Show K-40 kit version	K-40 Base unit	K-42H kit	K-42UC kit
Part number	7488 000 315	7488 000 330	7488 000 312
Transmitters included	-	2x HDMI	2x USB-C
Wireless mirroring of screen content (BYOD)	yes		
Wireless transmission of USB camera/audio (BYOM)	-		
Compatible transmitters	HDMI, USB-C, 4K HDMI, 4K USB-C, USB-A*	HDMI, USB-C, 4K HDMI, 4K USB-C, USB-A*	HDMI, USB-C, 4K HDMI, 4K USB-C, USB-A*
Windows 10 / 11	Transmitter / Klick&Show app for Windows / Googlecast / Miracast (with optional Miracast USB WiFi adapter)		
macOS	Transmitter / Klick&Show app for macOS / AirPlay / Googlecast		
Mobile devices	USB-C transmitter (DP ALT mode required) / Android app / AirPlay / Googlecast / Miracast (with optional Miracast USB WiFi adapter)		
Miracast support	optional, supports Miracast-Direct (P2P) and Miracast-over-Infrastructure (MS MICE)		
Maximum resolution, wireless	4K: with 4K transmitter 1080p: with Full-HD transmitter / Klick&Show app / Airplay / Miracast / Googlecast		
Simultaneous connections RJ45	> 30		
Simultaneous connections internal WLAN	≤ 16		
Splitscreen	up to 4 simultaneously, layout adjustable		
Low latency mouse cursor	yes, USB-A* transmitter and Klick&Show app for Windows / macOS		
Touch-Back /USB-HID support	yes, e.g. for use with interactive displays (touchscreens), whiteboards or projectors		
WiFi frequency band	2.4 / 5 GHz		
WiFi standard	WiFi 5 (IEEE 802.11b/g/n/ac)		
WiFi antennas	2x2 MIMO		
WiFi bandwidth	up to 1200 Mbps		
Security standard	WiFi: WPA PSK, WPA2 PSK - Video transmission encrypted with AES-256 bit + RSA1024 bit		
HDMI output	1x HDMI 2.0 / 3840x2160@60/30 Hz, 1920x1080@60Hz, 1280x720@60Hz		
HDCP version	HDCP 1.4, HDCP 2.0		
HDMI input / max. resolution	via HDMI transmitter (4K30 or 1080p60)		
Audio input	Transmitter / Klick&Show app / AirPlay / Googlecast / Miracast (with optional Miracast USB WiFi adapter)		
Audio output (analog)	1x 3.5 mm stereo jack		
USB 2.0 (type C)	1x (front)		
USB 2.0 (type A)	1x (front)		
USB 3.0 (type A)	1x (rear)		
LAN (RJ45)	1x 1000 Mbps with PoE, 1x 100 Mbps		
PoE standard	IEEE802.3af		
Control	Network: Web GUI, Telnet; RS232: 1x 3-pin Euroblock (rear)		
Housing / color	Aluminium, plastic / similar to Space Grey, black		
Dimensions (W x D x H)	165 x 95 x 25 mm (incl. antennas 165 x 215 x 25 mm)		
Weight	0.38 kg		
Power supply unit	plug-in power supply with interchangeable plugs (Euro AV, UK, US), 12 V / 1.5 A		
Power consumption	max. 18 W		

*discontinued since August 2023

Kindermann GmbH

Mainparkring 3 | D-97246 Eibelstadt | Germany

Email: info@kindermann.de

Subject to alterations | 7488000315 / 7488000330 / 7488000312 | 08.2024

www.kindermann.com